

## VRF Indoor units - 4-Way Cassettes

- Unobtrusive and flexible, blends in with any room decor
- Four-way adjustable grille
- Innovative air flow control and new panel design prevent dust accumulation on the ceiling
- Louvre and grille are easily detachable
- Corner pockets in all four corners for easy access
- Flexible installation - ideal for sites with restricted space above the ceiling
- High-lift drain pump (850 mm)



Indoor unit MMU Fascia panel		AP0092H RBC-U31PG(W)-E	AP0122H RBC-U31PG(W)-E	AP0152H RBC-U31PG(W)-E	AP0182H RBC-U31PG(W)-E	AP0242H RBC-U31PG(W)-E
Capacity code	hp	1	1.25	1.7	2	2.5
Cooling capacity	kW	2.8	3.6	4.5	5.6	7.1
Heating capacity	kW	3.2	4.0	5.0	6.3	8.0
Power input	kW	0.021	0.021	0.023	0.026	0.036
Air flow (high/medium/low)	l/s	222/203/189	222/203/189	258/231/219	292/256/222	358/256/222
Air flow (high/medium/low)	m³/h	800/730/680	800/730/680	930/830/790	1050/920/800	1290/920/800
Sound pressure level (high/medium/low)	dB(A)	30/29/27	30/29/27	31/29/27	32/29/27	35/31/28
Sound power level (high/medium/low)	dB(A)	45/44/42	45/44/42	46/44/42	47/44/42	50/46/43
Dimensions, height x width x depth	mm	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840
Weight	kg	18	18	20	20	20
Max. operating current	A	0.23	0.23	0.27	0.29	0.38
Starting current	A	0.30	0.30	0.33	0.36	0.42
Suggested fuse size	A	3	3	3	3	3
Power supply	V-ph-Hz	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50

Indoor unit MMU Fascia panel		AP0272H RBC-U31PG(W)-E	AP0302H RBC-U31PG(W)-E	AP0362H RBC-U31PG(W)-E	AP0482H RBC-U31PG(W)-E	AP0562H RBC-U31PG(W)-E
Capacity code	hp	3	3.2	4	5	6
Cooling capacity	kW	8.0	9.0	11.2	14.0	16.0
Heating capacity	kW	9.0	10.0	12.5	16.0	18.0
Power input	kW	0.036	0.043	0.088	0.112	0.112
Air flow (high/medium/low)	l/s	358/256/222	367/308/236	547/397/297	592/397/314	592/422/342
Air flow (high/medium/low)	m³/h	1290/920/800	1320/1110/850	1970/1430/1070	2130/1430/1130	2130/1520/1230
Sound pressure level (high/medium/low)	dB(A)	35/31/28	38/33/30	48/38/32	46/38/33	45/40/34
Sound power level (high/medium/low)	dB(A)	50/46/43	53/48/45	58/53/47	61/53/48	61/53/48
Dimensions, height x width x depth	mm	256 x 840 x 840	256 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840
Weight	kg	20	20	25	25	25
Max. operating current	A	0.38	0.43	0.73	0.88	0.92
Starting current	A	0.42	0.59	0.88	1.23	1.23
Suggested fuse size	A	3	3	3	3	3
Power supply	V-ph-Hz	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50