

## VRF Indoor units - Concealed Chassis Units

- The perfect solution for perimeter walls
- Can be hidden behind a decorative panel to blend in with any room surroundings
- Ideal for offices, libraries, hospitals and commercial buildings with large load fluctuations
- Extremely compact design, saving valuable space
- Low operating noise level - to 32 dB(A)
- Easy maintenance: removable split front panel and easy access from the right-hand side



Indoor unit MML		AP0071BH	AP0091BH	AP0121BH	AP0151BH	AP0181BH	AP0241BH
Capacity code	hp	0.8	1	1.25	1.7	2	2.5
Cooling capacity	kW	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	kW	2.5	3.2	4.0	5.0	6.3	8.0
Power input	kW	0.056	0.056	0.056	0.090	0.090	0.095
Air flow (high/medium/low)	l/s	128/111/83	128/111/83	128/111/83	206/167/136	206/167/136	264/220/178
Air flow (high/medium/low)	m³/h	460/400/300	460/400/300	460/400/300	740/600/490	740/600/490	950/790/640
Sound pressure level (high/medium/low)	dB(A)	36/34/32	36/34/32	36/34/32	36/34/32	36/34/32	42/37/33
Sound power level (high/medium/low)	dB(A)	49/47/45	49/47/45	49/47/45	49/47/45	49/47/45	55/50/46
Dimensions, height x width x depth	mm	600 x 745 x 220	600 x 745 x 220	600 x 745 x 220	600 x 1045 x 220	600 x 1045 x 220	600 x 1045 x 220
Weight	kg	21	21	21	29	29	29
Max. operating current	A	0.25	0.25	0.25	0.45	0.45	0.46
Starting current	A	0.60	0.60	0.60	0.80	0.80	1.00
Suggested fuse size	A	3	3	3	3	3	3
Power supply	V-ph-Hz	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50

