

VRF Indoor units - High Static Pressure Ducted Units

- Extremely powerful ducted model
- Flexible and compact design
- Unobtrusive installation in the ceiling void
- Ideal solution for both new and refurbished buildings
- Simple and fast installation
- Inspection hole allows access for easy maintenance
- Static pressure from 68 to 196 Pa



Indoor unit MMD		AP0181H	AP0241H	AP0271H	AP0361H	AP0481H
Capacity code	hp	2	2.5	3	4	5
Cooling capacity	kW	5.6	7.1	8.0	11.2	14.0
Heating capacity	kW	6.3	8.0	9.0	12.5	16.0
Power input	kW	0.184	0.299	0.299	0.368	0.414
Air flow (high/medium/low)	l/s	300/250/200	439/367/295	439/367/295	533/445/356	700/583/467
Air flow (high/medium/low)	m ³ /h	1080/900/720	1580/1320/1060	1580/1320/1060	1920/1600/1280	2520/2100/1680
Sound pressure level (high/medium/low)	dB(A)	37/35/33	40/38/36	40/38/36	40/38/36	40/38/36
Sound power level (high/medium/low)	dB(A)	50/48/46	53/51/49	53/51/49	53/51/49	53/51/49
Dimensions, height x width x depth	mm	380 x 850 x 660	380 x 850 x 660	380 x 850 x 660	380 x 850 x 660	380 x 1200 x 660
Weight	kg	50	52	52	56	67
Max. operating current	A	0.81	1.35	1.35	1.63	1.84
Starting current	A	1.3	3.5	3.5	4.1	4.8
Suggested fuse size	A	3	5	5	5	10
Power supply	V-ph-Hz	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50

Indoor unit MMU		AP0721H	AP0961H
Capacity code	hp	8	10
Cooling capacity	kW	22.4	28.0
Heating capacity	kW	25.0	31.5
Power input	kW	1.200	1.260
Air flow (high/medium/low)	l/s	1200/1000/800	1400/1167/933
Air flow (high/medium/low)	m ³ /h	4320/3600/2880	5040/4200/3360
Sound pressure level (high/medium/low)	dB(A)	49/47/45	50/48/46
Sound power level (high/medium/low)	dB(A)	62/60/58	63/61/59
Dimensions, height x width x depth	mm	470 x 1380 x 1250	470 x 1380 x 1250
Weight	kg	150	150
Max. operating current	A	5.25	5.52
Starting current	A	13.6	14.8
Suggested fuse size	A	16	16
Power supply	V-ph-Hz	220/240-1-50	220/240-1-50