

Toshiba Air Conditioning are pleased to introduce the NEW Higher Efficiency range of RAS multi outdoor units.



The RAS-M**UAV-E

The RAS-M**UAV-E has the following benefits and key features.

- Wide Range Of Indoor Units, Style & Capacity
- COP Increased By Up To 30%*
- Lightweight 41Kg
- Compliant With CE, RoHS, WEEE, AS & GOST



Brief Summary of Specification.

Model Number.	RAS-M18UAV-E	RAS-3M26GAV-E	RAS-4M27UAV-E	RAS-5M34UAV-E
Size (Height x Width x Depth mm)	550 x 780 x 290	795 x 900 x 320	890 x 900 x 320	890 x 900 x 320
Available Date.				
Retail Price ex VAT.				

Note * RAS-M18UAV-E = COP



Product Update R717-1102 1 of 8 17/02/2011

For further details, please contact TCUK Customer Services on 0870 8430333 or your local sales representative.

The manufacturer reserves the right to change the product specifications and information without notice.

Specification

OUTDOOR UNIT MODEL	RAS-M18UAV-E	RAS-3M26GAV-E	RAS-4M27UAV-E	RAS-5M34UAV-E
Sound Pressure levels dB(A)	51	49	49	51
Sound Power levels dB(A)	61	61	69	69
Operating Range °c (cooling)	5 to 43	10 to 43	10 to 43	10 to 43
Operating Range °c (heating)	-15 to 24	-15 to 21	-15 to 22	-10 to 22
Maximum Pipe Length (mtrs)	20	25	15	25
Changeless Pipe length (mtrs)	20	50	40	40
Flare Connections (gas – liquid)	3/8 - 1/4	3/8 – 1/4	1/2 – 1/4	1/2 - 1/4
Dimensions H x W x D (mm)	550x780x290	795x900x320	890x900x320	890x900x320
Weight (kgs)	41	64	75	75
Power Supply	220/240-1-50	220/240-1-50	220/240-1-50	220/240-1-50

RAS-M18UAV-E <Cooling>															
Power Voltage (V)	Operating Status	Combination				Unit Capacity (kW)				Cooling Capacity (kW)	Power Input (W)	Running Current (A)	Rated EER	CDU Sound Pressure (dB)	CDU Sound Power (dB)
		A	B	C	D	A	B	C	D						
230	1 Unit Operation	10	-	-	-	2.7	-	-	-	2.7 (1.1-3.2)	630 (220-800)	3.10 (1.37-3.66)	4.29	45	61
		13	-	-	-	3.7	-	-	-	3.7 (1.1-3.7)	1100 (220-1400)	5.00 (1.37-6.21)	3.36	49	64
		16	-	-	-	4.5	-	-	-	4.5 (1.1-4.5)	1500 (220-1700)	6.70 (1.37-7.23)	3.00	49	64
	2 Unit Operation	10	10	-	-	2.55	2.55	-	-	5.1 (1.4-6.1)	1410 (260-2150)	6.45 (1.61-9.54)	3.62	49	64
		13	10	-	-	3.00	2.20	-	-	5.2 (1.4-6.2)	1440 (260-2170)	6.45 (1.61-9.63)	3.61	49	64
		16	10	-	-	3.25	1.95	-	-	5.2 (1.4-6.2)	1440 (260-2170)	6.45 (1.61-9.63)	3.61	49	64
		13	13	-	-	2.60	2.60	-	-	5.2 (1.4-6.2)	1440 (260-2170)	6.45 (1.61-9.63)	3.61	49	64
		16	13	-	-	2.85	2.35	-	-	5.2 (1.4-6.2)	1440 (260-2170)	6.45 (1.61-9.63)	3.61	49	64
	RAS-M18UAV-E <Heating>														
	Power Voltage (V)	Operating Status	Combination				Unit Capacity (kW)				Heating Capacity (kW)	Power Input (W)	Running Current (A)	Rated COP	CDU Sound Pressure (dB)
A			B	C	D	A	B	C	D						
230	1 Unit Operation	10	-	-	-	4.0	-	-	-	4.0 (0.7-5.2)	1200 (170-1700)	5.40 (1.06-7.54)	3.33	51	66
		13	-	-	-	5.0	-	-	-	5.0 (0.7-6.5)	1800 (170-2530)	8.10 (1.06-11.22)	2.76	51	66
		16	-	-	-	5.5	-	-	-	5.5 (0.7-6.9)	1900 (170-2530)	8.50 (1.06-11.22)	2.89	51	66
	2 Unit Operation	10	10	-	-	2.70	2.70	-	-	5.4 (0.9-8.2)	1190 (200-2530)	5.35 (1.24-11.22)	4.54	51	66
		13	10	-	-	3.11	2.49	-	-	5.6 (0.9-8.3)	1190 (200-2530)	5.35 (1.24-11.22)	4.71	51	66
		16	10	-	-	3.24	2.36	-	-	5.6 (0.9-8.3)	1190 (200-2530)	5.35 (1.24-11.22)	4.71	51	66
		13	13	-	-	2.60	2.80	-	-	5.6 (0.9-8.3)	1190 (200-2530)	5.35 (1.24-11.22)	4.71	51	66
		16	13	-	-	2.93	2.67	-	-	5.6 (0.9-8.3)	1190 (200-2530)	5.35 (1.24-11.22)	4.71	51	66



Product Update R717-1102 2 of 8 17/02/2011

For further details, please contact TCUK Customer Services on 0870 8430333 or your local sales representative.

The manufacturer reserves the right to change the product specifications and information without notice.

RAS-3M26GAV-E <Cooling>													
Power Voltage (V)	Operating Status	Combination				Unit Capacity (kW)				Cooling Capacity (kW)	Power Input (W)	Running Current (A)	CDU Sound Pressure (dB)
		A	B	C	D	A	B	C	D				
230	1 Unit Operation	10	-	-	-	2.7	-	-	-	2.7	750	3.71	48
		13	-	-	-	3.7	-	-	-	3.7	1200	5.49	48
		16	-	-	-	4.5	-	-	-	4.5	1650	7.47	48
	2 Unit Operation	10	10	-	-	2.70	2.70	-	-	5.4	1530	6.79	48
		13	10	-	-	3.41	2.49	-	-	5.9	1810	8.03	48
		16	10	-	-	3.94	2.36	-	-	6.3	2040	9.05	48
		13	13	-	-	3.15	3.15	-	-	6.3	2040	9.05	48
		16	13	-	-	3.73	3.07	-	-	6.8	2040	10.29	48
	3 Unit Operation	16	16	-	-	3.60	3.60	-	-	7.2	2320	11.31	48
		10	10	10	-	2.47	2.47	2.47	-	7.4	2550	9.98	48
		13	10	10	-	3.01	2.20	2.20	-	7.4	2230	9.98	48
		16	10	10	-	3.36	2.02	2.02	-	7.4	2230	9.98	48
		13	10	10	-	2.71	2.71	1.98	-	7.4	2230	9.98	48
		16	13	10	-	3.10	2.55	1.86	-	7.5	2230	9.98	48
		13	13	13	-	2.50	2.50	2.50	-	7.5	2250	9.98	48
		16	16	10	-	2.88	2.88	1.73	-	7.5	2250	9.98	48
		16	13	13	-	2.84	2.33	2.33	-	7.5	2250	9.98	48
		16	16	13	-	2.66	2.66	2.19	-	7.5	2250	9.98	48
		RAS-3M26GAV-E <Heating>											
Power Voltage (V)	Operating Status	Combination				Unit Capacity (kW)				Heating Capacity (kW)	Power Input (W)	Running Current (A)	CDU Sound Pressure (dB)
		A	B	C	D	A	B	C	D				
230	1 Unit Operation	10	-	-	-	4.0	-	-	-	4.0	1500	6.65	48
		13	-	-	-	5.0	-	-	-	5.0	2050	9.09	48
		16	-	-	-	5.5	-	-	-	5.5	2400	10.65	48
	2 Unit Operation	10	10	-	-	3.60	3.60	-	-	7.2	2050	9.09	48
		13	10	-	-	4.22	3.38	-	-	7.6	2240	9.94	48
		16	10	-	-	4.57	3.33	-	-	7.9	2380	10.56	48
		13	13	-	-	3.95	3.95	-	-	7.9	2380	10.56	48
		16	13	-	-	4.35	3.95	-	-	8.3	2560	11.36	48
	3 Unit Operation	16	16	-	-	4.30	4.30	-	-	8.6	2700	11.98	48
		10	10	10	-	2.87	2.87	2.87	-	8.6	2300	10.20	48
		13	10	10	-	3.35	2.68	2.68	-	8.7	2360	10.47	48
		16	10	10	-	3.59	2.61	2.61	-	8.8	2430	10.78	48
		13	10	10	-	3.14	3.14	2.51	-	8.8	2430	10.78	48
		16	13	10	-	3.34	3.03	2.43	-	8.8	2430	10.78	48
		13	13	13	-	2.93	2.93	2.93	-	8.8	2430	10.78	48
		16	16	10	-	3.26	3.26	2.37	-	8.9	2490	11.05	48
		16	13	13	-	3.16	2.87	2.87	-	8.9	2490	11.05	48
		16	16	13	-	3.09	3.09	2.81	-	9.0	2550	11.31	48

RAV-4M27UAV-E <Cooling>													
Power Voltage (V)	Operating Status	Combination				Unit Capacity (kW)				Cooling Capacity (kW)	Power Input (W)	Running Current (A)	CDU Sound Pressure (dB)
		A	B	C	D	A	B	C	D				
230	1 Unit Operation	10	-	-	-	2.7	-	-	-	2.7	750	3.71	48
		13	-	-	-	3.7	-	-	-	3.7	1200	5.49	48
		16	-	-	-	4.5	-	-	-	4.5	1650	7.47	48
	2 Unit Operation	10	10	-	-	2.70	2.70	-	-	5.4	1530	6.79	48
		13	10	-	-	3.41	2.49	-	-	5.9	1810	8.03	48
		16	10	-	-	3.94	2.36	-	-	6.3	2040	9.05	48
		13	13	-	-	3.15	3.15	-	-	6.3	2040	9.05	48
		16	13	-	-	3.73	3.07	-	-	6.8	2320	10.29	48
	3 Unit Operation	16	16	-	-	3.60	3.60	-	-	7.2	2550	11.31	48
		10	10	10	-	2.53	2.53	2.53	-	7.6	2400	10.65	48
		13	10	10	-	3.13	2.28	2.28	-	7.7	2410	10.69	48
		16	10	10	-	3.50	2.10	2.10	-	7.7	2410	10.69	48
		13	10	10	-	2.82	2.82	2.06	-	7.7	2410	10.69	48
		16	13	10	-	3.22	2.65	1.93	-	7.8	2430	10.78	48
		13	13	13	-	2.60	2.60	2.60	-	7.8	2430	10.78	48
		16	16	10	-	3.04	3.04	1.82	-	7.9	2440	10.83	48
		16	13	13	-	2.99	2.46	2.46	-	7.9	2440	10.83	48
		16	16	13	-	2.80	2.80	2.30	-	7.9	2440	10.83	48
		16	16	16	-	2.67	2.67	2.67	-	8.0	2450	10.87	48
	4 Unit Operation	10	10	10	10	1.98	1.98	1.98	1.98	7.9	2450	10.87	48
		13	10	10	10	2.48	1.81	1.81	1.81	7.9	2450	10.87	48
		16	10	10	10	2.86	1.71	1.71	1.71	8.0	2500	11.09	48
		13	13	10	10	2.31	2.31	1.69	1.69	8.0	2500	11.09	48
		16	13	10	10	2.65	2.18	1.59	1.59	8.0	2500	11.09	48
		13	13	13	10	2.14	2.14	2.14	1.57	8.0	2500	11.09	48
		16	13	13	10	2.47	2.03	2.03	1.48	8.0	2500	11.09	48
		13	13	13	13	2.00	2.00	2.00	2.00	8.0	2500	11.09	48
16		16	10	10	2.50	2.50	1.50	1.50	8.0	2500	11.09	48	



Product Update R717-1102 4 of 8 17/02/2011

For further details, please contact TCUK Customer Services on 0870 8430333 or your local sales representative.

The manufacturer reserves the right to change the product specifications and information without notice.

RAV-4M27UAV-E <Heating>														
Power Voltage (V)	Operating Status	Combination				Unit Capacity (kW)				Heating Capacity (kW)	Power Input (W)	Running Current (A)	CDU Sound Pressure (dB)	
		A	B	C	D	A	B	C	D					
230	1 Unit Operation	10	-	-	-	4.0	-	-	-	4.0	1450	6.43	48	
		13	-	-	-	5.0	-	-	-	5.0	2050	9.09	48	
		16	-	-	-	5.5	-	-	-	5.5	2400	10.65	48	
	2 Unit Operation	10	10	-	-	3.60	3.60	-	-	7.2	2100	9.32	48	
		13	10	-	-	4.22	3.38	-	-	7.6	2320	10.29	48	
		16	10	-	-	4.57	3.33	-	-	7.9	2480	11.00	48	
		13	13	-	-	3.95	3.95	-	-	7.9	2480	11.00	48	
		16	13	-	-	4.35	3.95	-	-	8.3	2700	11.00	48	
		16	16	-	-	4.30	4.30	-	-	8.6	2860	11.98	48	
	3 Unit Operation	10	10	10	-	2.87	2.87	2.87	-	8.6	2300	12.69	48	
		13	10	10	-	3.35	2.68	2.68	-	8.7	2350	10.20	48	
		16	10	10	-	3.54	2.58	2.58	-	8.7	2350	10.43	48	
		13	10	10	-	3.11	3.11	2.49	-	8.7	2350	10.43	48	
		16	13	10	-	3.34	3.03	2.43	-	8.8	2400	10.43	48	
		13	13	13	-	2.93	2.93	2.93	-	8.8	2400	10.65	48	
		16	16	10	-	3.26	3.26	2.37	-	8.9	2450	10.65	48	
		16	13	13	-	3.16	2.87	2.87	-	8.9	2450	10.87	48	
		16	16	13	-	3.06	3.06	2.78	-	8.9	2450	10.87	48	
		16	16	16	-	3.00	3.00	3.00	-	9.0	25800	10.87	48	
		4 Unit Operation	10	10	10	10	2.23	2.23	2.23	2.23	8.9	2100	11.09	48
			13	10	10	10	2.62	2.09	2.09	2.09	8.9	2100	9.32	48
	16		10	10	10	2.83	2.06	2.06	2.06	9.0	2250	9.32	48	
	13		13	10	10	2.50	2.50	2.00	2.00	9.0	2250	9.98	48	
	16		13	10	10	2.68	2.43	1.95	1.95	9.0	2250	9.98	48	
	13		13	13	10	2.37	2.37	2.37	1.89	9.0	2250	9.98	48	
	16		13	13	10	2.54	2.31	2.31	1.85	9.0	2250	9.98	48	
	13		13	13	13	2.25	2.25	2.25	2.25	9.0	2250	9.98	48	
	16	16	10	10	2.61	2.61	1.89	1.89	9.0	2250	9.98	48		



Product Update R717-1102 5 of 8 17/02/2011

For further details, please contact TCUK Customer Services on 0870 8430333 or your local sales representative.

The manufacturer reserves the right to change the product specifications and information without notice.

RAV-5MUAV-E <Cooling>																
Power Voltage (V)	Operating Status	Combination					Unit Capacity (kW)					Cooling Capacity (kW)	Power Input (W)	Running Current (A)	CDU Sound Pressure (dB)	
		A	B	C	D	E	A	B	C	D	E					
230	1 Unit Operation	10	-	-	-	-	2.7	-	-	-	-	2.7	750	4.23	51	
		13	-	-	-	-	3.7	-	-	-	-	3.7	1200	5.93	51	
		16	-	-	-	-	4.5	-	-	-	-	4.5	1650	7.63	51	
		18	-	-	-	-	5.0	-	-	-	-	5.0	1950	8.92	51	
	2 Unit Operation	10	10	-	-	-	2.70	2.70	-	-	-	5.4	1530	7.00	51	
		13	10	-	-	-	3.41	2.49	-	-	-	5.9	1810	8.28	51	
		16	10	-	-	-	3.94	2.36	-	-	-	6.3	2040	9.34	51	
		18	10	-	-	-	4.09	2.21	-	-	-	6.3	2040	9.34	51	
		13	13	-	-	-	3.15	3.15	-	-	-	6.3	2040	9.34	51	
		16	13	-	-	-	3.73	3.07	-	-	-	6.8	2320	10.62	51	
		18	13	-	-	-	3.91	2.89	-	-	-	6.8	2320	10.62	51	
		16	16	-	-	-	3.60	3.60	-	-	-	7.2	2550	11.67	51	
		18	16	-	-	-	3.79	3.41	-	-	-	7.2	2550	11.67	51	
		18	18	-	-	-	3.60	3.60	-	-	-	7.2	2550	11.67	51	
	3 Unit Operation	10	10	10	-	-	2.53	2.53	2.53	-	-	7.6	2400	10.98	51	
		13	10	10	-	-	3.13	2.28	2.28	-	-	7.7	2410	11.03	51	
		16	10	10	-	-	3.50	2.10	2.10	-	-	7.7	2410	11.03	51	
		18	10	10	-	-	3.70	2.00	2.00	-	-	7.7	2410	11.03	51	
		13	13	10	-	-	2.82	2.82	2.06	-	-	7.7	2410	11.03	51	
		16	13	10	-	-	3.22	2.65	1.93	-	-	7.8	2430	11.12	51	
		18	13	10	-	-	3.42	2.53	1.85	-	-	7.8	2430	11.12	51	
		16	16	10	-	-	3.04	3.04	1.82	-	-	7.9	2440	11.17	51	
		18	16	10	-	-	3.20	2.88	1.73	-	-	7.8	2430	11.12	51	
		18	18	10	-	-	3.11	3.11	1.68	-	-	7.9	2440	11.17	51	
		13	13	13	-	-	2.60	2.60	2.60	-	-	7.8	2430	11.12	51	
		16	13	13	-	-	2.99	2.46	2.46	-	-	7.9	2440	11.17	51	
		18	13	13	-	-	3.19	2.36	2.36	-	-	7.9	2440	11.17	51	
		16	16	13	-	-	2.80	2.80	2.30	-	-	7.9	2440	11.17	51	
		18	16	13	-	-	2.99	2.69	2.21	-	-	7.9	2440	11.17	51	
		18	18	13	-	-	2.88	2.88	2.13	-	-	7.9	2440	11.17	51	
		4 Unit Operation	10	10	10	10	-	1.98	1.98	1.98	1.98	-	7.9	2450	11.21	51
			13	10	10	10	-	2.48	1.81	1.81	1.81	-	7.9	2450	11.21	51
	16		10	10	10	-	2.86	1.71	1.71	1.71	-	8.0	2500	11.44	51	
	18		10	10	10	-	3.05	1.65	1.65	1.65	-	8.0	2500	11.44	51	
	13		13	10	10	-	2.31	2.31	1.69	1.69	-	8.0	2500	11.44	51	
	16		13	10	10	-	2.65	2.18	1.59	1.59	-	8.0	2500	11.44	51	
	16		16	10	10	-	2.50	2.50	1.50	1.50	-	8.0	2500	11.44	51	
	18		13	10	10	-	2.84	2.10	1.53	1.53	-	8.0	2500	11.44	51	
	18		16	10	10	-	2.68	2.42	1.45	1.45	-	8.0	2500	11.44	51	
	18		18	10	10	-	2.60	2.60	1.40	1.40	-	8.0	2500	11.44	51	
	13		13	13	10	-	2.14	2.14	1.57	1.57	-	8.0	2500	11.44	51	
	16		13	13	10	-	2.47	2.03	1.48	1.48	-	8.0	2500	11.44	51	
	16		16	13	10	-	2.34	2.34	1.92	1.40	-	8.0	2500	11.44	51	
	18		13	13	10	-	2.65	1.96	1.96	1.43	-	8.0	2500	11.44	51	
	18		16	13	10	-	2.52	2.26	1.86	1.36	-	8.0	2500	11.44	51	
	18		18	13	10	-	2.44	2.44	1.80	1.32	-	8.0	2500	11.44	51	
	13		13	13	13	-	2.00	2.00	2.00	2.00	-	8.0	2500	11.44	51	
	16		13	13	13	-	2.31	1.90	1.90	1.90	-	8.0	2500	11.44	51	
	18		13	13	13	-	2.48	1.84	1.84	1.84	-	8.0	2500	11.44	51	
	16		16	13	13	-	2.20	2.20	1.80	1.80	-	8.0	2500	11.44	51	
18	16	13	13	-	2.37	2.13	1.75	1.75	-	8.0	2500	11.44	51			
18	18	13	13	-	2.30	2.30	1.70	1.70	-	8.0	2500	11.44	51			
5 Unit Operation	10	10	10	10	10	1.98	1.98	1.98	1.98	1.98	9.9	2894	13.24	51		
	13	10	10	10	10	2.53	1.84	1.84	1.84	1.84	9.9	2894	13.24	51		
	16	10	10	10	10	2.91	1.75	1.75	1.75	1.75	9.9	2894	13.24	51		
	18	10	10	10	10	3.13	1.69	1.69	1.69	1.69	9.9	2894	13.24	51		
	13	13	10	10	10	2.36	2.36	1.72	1.72	1.72	9.9	2894	13.24	51		
	16	13	10	10	10	2.73	2.25	1.64	1.64	1.64	9.9	2894	13.24	51		
	18	13	10	10	10	2.95	2.18	1.59	1.59	1.59	9.9	2894	13.24	51		
	16	16	10	10	10	2.61	2.61	1.56	1.56	1.56	9.9	2894	13.24	51		
	13	13	13	10	10	2.22	2.22	1.62	1.62	1.62	9.9	2894	13.24	51		
	16	13	13	10	10	2.58	2.12	1.55	1.55	1.55	9.9	2894	13.24	51		
	18	13	13	10	10	2.78	2.06	1.50	1.50	1.50	9.9	2894	13.24	51		
	16	16	13	10	10	2.49	2.49	1.49	1.49	1.49	10.0	2932	13.38	51		
	13	13	13	13	10	2.09	2.09	2.09	2.09	2.09	9.9	2894	13.24	51		
	16	13	13	13	10	2.46	2.02	2.02	2.02	2.02	10.0	2932	13.38	51		
	18	13	13	13	10	2.66	1.97	1.97	1.97	1.97	10.0	2932	13.38	51		
	16	16	13	13	10	2.36	2.36	1.94	1.94	1.94	10.0	2932	13.38	51		
	13	13	13	13	13	2.00	2.00	2.00	2.00	2.00	10.0	2932	13.38	51		
	16	13	13	13	13	2.33	1.92	1.92	1.92	1.92	10.0	2932	13.38	51		

RAV-5M34UAV-E <Heating>															
Power Voltage (V)	Operating Status	Combination					Unit Capacity (kW)					Cooling Capacity (kW)	Power Input (W)	Running Current (A)	CDU Sound Pressure (dB)
		A	B	C	D	E	A	B	C	D	E				
230	1 Unit Operation	10	-	-	-	-	4.0	-	-	-	-	4.0	1450	6.64	54
		13	-	-	-	-	5.0	-	-	-	-	5.0	2050	9.38	54
		16	-	-	-	-	5.5	-	-	-	-	5.5	2400	10.98	54
		18	-	-	-	-	6.0	-	-	-	-	6.0	2630	12.04	54
	2 Unit Operation	10	10	-	-	-	3.60	3.60	-	-	-	7.2	2100	9.61	54
		13	10	-	-	-	4.22	3.38	-	-	-	7.6	2320	10.62	54
		16	10	-	-	-	4.57	3.33	-	-	-	7.9	2480	11.35	54
		18	10	-	-	-	4.74	3.16	-	-	-	7.9	2480	11.35	54
		13	13	-	-	-	3.95	3.95	-	-	-	7.9	2480	11.35	54
		16	13	-	-	-	4.35	3.95	-	-	-	8.3	2700	12.36	54
		18	13	-	-	-	4.53	3.77	-	-	-	8.3	2700	12.36	54
		16	16	-	-	-	4.30	4.30	-	-	-	8.6	2860	13.09	54
		18	16	-	-	-	4.49	4.11	-	-	-	8.6	2860	13.09	54
		18	18	-	-	-	4.30	4.30	-	-	-	8.6	2860	13.09	54
	3 Unit Operation	10	10	10	-	-	2.87	2.87	2.87	-	-	8.6	2300	10.53	54
		13	10	10	-	-	3.35	2.68	2.68	-	-	8.7	2350	10.76	54
		16	10	10	-	-	3.54	2.58	2.58	-	-	8.7	2350	10.76	54
		18	10	10	-	-	3.73	2.49	2.49	-	-	8.7	2350	10.76	54
		13	13	10	-	-	3.11	3.11	2.49	-	-	8.7	2350	10.76	54
		16	13	10	-	-	3.34	3.03	2.43	-	-	8.8	2400	10.98	54
		18	13	10	-	-	3.52	2.93	2.35	-	-	8.8	2400	10.98	54
		16	16	10	-	-	3.26	3.26	2.37	-	-	8.9	2450	11.21	54
		18	16	10	-	-	3.45	3.16	2.30	-	-	8.9	2450	11.21	54
		18	18	10	-	-	3.34	3.34	2.23	-	-	8.9	2450	11.21	54
		13	13	13	-	-	2.93	2.93	2.93	-	-	8.8	2400	10.98	54
		16	13	13	-	-	3.16	2.87	2.87	-	-	8.9	2450	11.21	54
		18	13	13	-	-	3.34	2.78	2.78	-	-	8.9	2450	11.21	54
		16	16	13	-	-	3.06	3.06	2.78	-	-	8.9	2450	11.21	54
		18	16	13	-	-	3.24	2.97	2.70	-	-	8.9	2450	11.21	54
		18	18	13	-	-	3.14	3.14	2.62	-	-	8.9	2450	11.21	54
		10	10	10	10	-	2.23	2.23	2.23	2.23	-	8.9	2100	9.61	54
		13	10	10	10	-	2.62	2.09	2.09	2.09	-	8.9	2100	9.61	54
		16	10	10	10	-	2.83	2.06	2.06	2.06	-	9.0	2250	10.30	54
		18	10	10	10	-	3.00	2.00	2.00	2.00	-	9.0	2250	10.30	54
	13	13	10	10	-	2.50	2.50	2.00	2.00	-	9.0	2250	10.30	54	
	16	13	10	10	-	2.68	2.43	1.95	1.95	-	9.0	2250	10.30	54	
	16	16	10	10	-	2.61	2.61	1.89	1.89	-	9.0	2250	10.30	54	
	18	13	10	10	-	2.84	2.37	1.89	1.89	-	9.0	2250	10.30	54	
	18	16	10	10	-	2.77	2.54	1.85	1.85	-	9.0	2250	10.30	54	
	18	18	10	10	-	2.70	2.70	1.80	1.80	-	9.0	2250	10.30	54	
	13	13	13	10	-	2.37	2.37	2.37	1.89	-	9.0	2250	10.30	54	
	16	13	13	10	-	2.54	2.31	2.31	1.85	-	9.0	2250	10.30	54	
	16	16	13	10	-	2.48	2.48	2.25	1.80	-	9.0	2250	10.30	54	
	18	13	13	10	-	2.70	2.25	2.25	1.80	-	9.0	2250	10.30	54	
	18	16	13	10	-	2.63	2.41	2.20	1.76	-	9.0	2250	10.30	54	
	18	18	13	10	-	2.57	2.57	2.14	1.71	-	9.0	2250	10.30	54	
	13	13	13	13	-	2.25	2.25	2.25	2.25	-	9.0	2250	10.30	54	
	16	13	13	13	-	2.41	2.20	2.20	2.20	-	9.0	2250	10.30	54	
	18	13	13	13	-	2.57	2.14	2.14	2.14	-	9.0	2250	10.30	54	
	16	16	13	13	-	2.36	2.36	2.14	2.14	-	9.0	2250	10.30	54	
	18	16	13	13	-	2.51	2.30	2.09	2.09	-	9.0	2250	10.30	54	
	18	18	13	13	-	2.45	2.45	2.05	2.05	-	9.0	2250	10.30	54	
	10	10	10	10	10	2.34	2.34	2.34	2.34	2.34	11.7	2762	12.64	54	
	13	10	10	10	10	2.79	2.23	2.23	2.23	2.23	11.7	2762	12.64	54	
	16	10	10	10	10	2.99	2.18	2.18	2.18	2.18	11.7	2762	12.64	54	
	18	10	10	10	10	3.19	2.13	2.13	2.13	2.13	11.7	2762	12.64	54	
	13	13	10	10	10	2.66	2.66	2.13	2.13	2.13	11.7	2762	12.64	54	
	16	13	10	10	10	2.86	2.60	2.08	2.08	2.08	11.7	2762	12.64	54	
	18	13	10	10	10	3.05	2.54	2.03	2.03	2.03	11.7	2762	12.64	54	
	16	16	10	10	10	2.80	2.80	2.03	2.03	2.03	11.7	2762	12.64	54	
	13	13	13	10	10	2.54	2.54	2.54	2.03	2.03	11.7	2762	12.64	54	
	16	13	13	10	10	2.74	2.49	2.49	1.99	1.99	11.7	2762	12.64	54	
	18	13	13	10	10	2.93	2.44	2.44	1.95	1.95	11.7	2762	12.64	54	
	16	16	13	10	10	2.75	2.75	2.50	2.00	2.00	12.0	2833	12.97	54	
	13	13	13	13	10	2.44	2.44	2.44	2.44	2.44	11.7	2762	12.64	54	
	16	13	13	13	10	2.69	2.45	2.45	2.45	2.45	12.0	2833	12.97	54	
	18	13	13	13	10	2.88	2.40	2.40	2.40	2.40	12.0	2833	12.97	54	
	16	16	13	13	10	2.64	2.64	2.40	2.40	2.40	12.0	2833	12.97	54	
	13	13	13	13	13	2.40	2.40	2.40	2.40	2.40	12.0	2833	12.97	54	
	16	13	13	13	13	2.59	2.35	2.35	2.35	2.35	12.0	2833	12.97	54	

TOSHIBA AIRCONDITIONING
Advancing the *eco*-evolution

Product Update R717-1102 8 of 8 17/02/2011

For further details, please contact TCUK Customer Services on 0870 8430333 or your local sales representative.

The manufacturer reserves the right to change the product specifications and information without notice.