

New Console Type Small Commercial R32

TOSHIBA are pleased to announce the launch of the NEW R32 Console Type unit to join the small commercial line-up



Accessory Wireless adapter
RB-N102S-G
Application
Toshiba Home AC Control

1. Line Up

Indoor Model	Outdoor Model (Common with SHORAI CDU for single split)	Cooling Capacity (KW)	Heating Capacity (kW)
RAS-B10U2FVG-E1	RAS-10PAVSG-E	2.50	3.20
RAS-B13U2FVG-E1	RAS-13PAVSG-E	3.50	4.20
RAS-B18U2FVG-E1	RAS-18PAVSG-E	5.00	6.00

2. Production

End of January 2019

3. Features

- Highlighted Features : Weekly timer, floor warming, bi-flow, air outlet selection, child lock, WiFi compatibility
- Standard Features : Swing, hi power, eco, self-cleaning, quiet FCU, silent CDU, manual defrost, self-diagnosis, heating only compatibility, power select, comfort sleep, fire place, 8°C, weekly timer, floor, preset
- Extra Features of the accessory controller : smart control WiFi via mobile application, temperature monitoring, fireplace, power select, on-off timer, 8°C, weekly schedule, all AC's and group control



TOSHIBA Air Conditioning offering total HVAC Solutions

**whatever
you need**

4. Specifications

Indoor		RAS-B10U2FVG-E1	RAS-B13U2FVG-E1	RAS-B18U2FVG-E1
Outdoor		RAS-10PAVSG-E	RAS-13PAVSG-E	RAS-18PAVSG-E
Power supply	(V/Ph/Hz)	220-240/1/50		
Capacity	(kW)	2.5	3.5	5.0
Power consumption	(kW)	0.6	1.10	1.75
EER		4.17	3.18	2.86
Pdesignc	(kW)	2.50	3.50	5.00
SEER		6.60	6.40	6.20
Indoor Noise	(dB)	39/26	40/27	46/34
Outdoor Noise	(dB)	46	48	49
Air Flow	(m³/min)	7.8	8.5	10.0
Capacity	(kW)	3.2	4.2	6.0
Power Consumption	(kW)	0.87	1.25	2.05
COP		3.68	3.36	2.93
Pdesignh	(kW)	2.50	3.00	4.00
SCOP		4.20	4.20	4.00
Indoor Noise	(dB)	39/26	40/27	46/34
Outdoor Noise	(dB)	47	50	50
Air Flow	(m³/min)	8.5	9.2	10.7
Dimensions Indoor H x W x D	(mm)	600 x 700 x 220		
Weight Indoor	(kg)	16	16	16
Dimensions Outdoor H x W x D	(mm)	550 x 780 x 290		
Weight Outdoor	(kg)	28	28	34
Chargeless	(m)	15	15	15
Max length	(m)	20	20	20
Max height	(m)	10	10	12
Refrigerant		R32		
Energy label	Cool/Heat	A++/A+		
Useable temp range	Cooling	Indoor : 21~32°C, Outdoor : (-15) ~ 46°C		
	Heating	Indoor : 0~28°C, Outdoor : (-15) ~ 24°C		

For further information please contact our customer support team on **0870 843 0333**, your local representative, your supplier of **TOSHIBA** products or email any enquiries to: - general.enquiries@toshiba-ac.com

